



SERIE LANTERNES LED UCP1

Spécifications Techniques

Modèles	UCP1-30W-3KD90	UCP1-60W-3KD90	UCP1-60W-4KD90
Puissance	30W	60W	60W
Led Chip	Philips LED Chip	Philips LED Chip	Philips LED Chip
Driver	Sosen	Meanwell	Meanwell
T° de Couleur	3000K	3000K	4000K
CRI	>70	>70	>70
Angle	90°	90°	90°
Alimentation	AC 100-277V	AC 100-277V	AC 100-277V
Facteur de Puissance	>0.95	>0.95	>0.95
Efficacité lumineuse	>135LM/W	>140LM/W	>150LM/W
Flux initial	>4000LM	>8400LM	>9000LM
Environnement de travail	-40°C ~+50°C	-40°C ~+50°C	-40°C ~+50°C
Durée de vie	>50, 000Hrs	>50, 000Hrs	>50, 000Hrs
IP Grade	IP66	IP66	IP66
IK Grade	IK08	IK08	IK08
Dimensions produit	Φ422*H539MM	Φ422*H539MM	Φ422*H539MM
Diamètre pôle	60-80mm	76mm	76mm
Quantité/Carton	2pcs	2pcs	2pcs
Poids Brut/Carton	14.0KGS	15.0KGS	15.0KGS
Dimensions/carton	54*49*51CM	54*49*51CM	54*49*51CM
Matériau	Aluminium Moulé	Aluminium Moulé	Aluminium Moulé

Garantie 5 ans

Détail Produit



Photos Produit- Installation

